



Specifications Eglo Connect.Z Smart  
Pendant Folcino-Z Steel Bronze, Black  
36W 3720lm - 827-865 Tunable White +  
RGB | Dimmable

[View Product](#)

General Information

|                          |                                        |
|--------------------------|----------------------------------------|
| SKU                      | 254547                                 |
| EAN                      | 9008606360284                          |
| Brand                    | Eglo                                   |
| Manufacturer Name        | LED-RGB/CCT HL BLACK/BRONZE 'FOLCINO-Z |
| Any Lamp all-in warranty | 5 Years                                |
| Average Lifetime (h)     | 15000                                  |

Technical Information

|                             |                                                                         |
|-----------------------------|-------------------------------------------------------------------------|
| Ecosystem Compatibility     | Amazon Alexa, Google Home, Philips Hue, Tuya (Smart Life), Caalex Smart |
| Lighting Control            | Zigbee                                                                  |
| Technology                  | LED Integrated                                                          |
| Voltage (V)                 | 220-240                                                                 |
| Wattage                     | 36                                                                      |
| Dimmable                    | Dimmable when using a Dimmable Bulb                                     |
| Colour Code                 | 827 Extra Warm White, 865 Daylight                                      |
| Colour temperature (Kelvin) | 2700 Extra Warm White, 6500 Daylight                                    |
| Colour Rendering (Ra)       | 80-89                                                                   |
| Colour of Light             | RGBW                                                                    |
| Light colour options        | Tunable White, RGB                                                      |
| Luminous Flux (Lumen)       | 3720                                                                    |

|                          |                  |
|--------------------------|------------------|
| Luminous Efficacy (lm/W) | 103.333333333333 |
|--------------------------|------------------|

|                 |         |
|-----------------|---------|
| Mounting Method | Pendant |
|-----------------|---------|

|                    |                   |
|--------------------|-------------------|
| Emergency Lighting | No Emergency Unit |
|--------------------|-------------------|

|                       |                         |
|-----------------------|-------------------------|
| Product Type Category | LED Decorative Lighting |
|-----------------------|-------------------------|

## Fixture Information

|                    |                |
|--------------------|----------------|
| Fixture Connection | Terminal block |
|--------------------|----------------|

|           |      |
|-----------|------|
| IP-rating | IP20 |
|-----------|------|

|                       |       |
|-----------------------|-------|
| Colour of the Fixture | Brass |
|-----------------------|-------|

|         |       |
|---------|-------|
| Housing | Steel |
|---------|-------|

|        |           |
|--------|-----------|
| Series | Connect.Z |
|--------|-----------|

## Dimensions

|             |     |
|-------------|-----|
| Length (mm) | 640 |
|-------------|-----|

|            |     |
|------------|-----|
| Width (mm) | 435 |
|------------|-----|

|             |      |
|-------------|------|
| Height (mm) | 1100 |
|-------------|------|

## Sensor Information

|                |           |
|----------------|-----------|
| Type of sensor | No Sensor |
|----------------|-----------|

## Why Any-lamp?



Order from the **largest lighting specialist** in Europe



**Customised** quotation



Up to **7 years warranty**



**Easy** return process

